



Model 214 Series A, B, C, & D

Standard Equipment

- 1/7th HP heavy duty DC motor.
 - Variable speed control unit (5 amp / 115 VAC).
 - Interchangeable spindle with linear sealed bearings for quick and easy spindle change. (No longer needs oiling)
- Models A-1 & B-1 include Yukiwa 0-5/32" keyed chuck.
 Models C-3 & D-3 include Yukiwa 0-1/8" keyless chuck.

Optional Equipment

- Dial depth gauge with 1/2" travel and AGD standard lug back for other inspection and test uses. (Models B & D)
- Foot Switch for the VSC.
- Hollow spindles for special applications.
- Chuck wedges for safe removal of chucks to prevent marring the spindle.
- Precision column stop for table.
- Reservoir base.

Specifications

Description	Dimension
Height With Depth Indicator	17"
Width	5-1/4"
Depth	11"
Chuck to Adjustable Table	5-3/4"
Chuck to Base	7"
Spindle Feed Travel	1-1/4"
Center To Column	2-1/2"
Table Size With Clamping Slots	4" x 4"
Table Center Hole	5/8"
Drill Size	0 - 5/32"
Hole Size (varies with chuck size)	.002 - 5/32"
Chuck Spindle Runout at Mounting Taper	Within .0002"
Weight / Shipping Weight	9 / 12 lbs.

CAMERON MICRO DRILL PRESSES, Division of Treat Enterprises
 19401 Rawhide Road, Sonora, CA 95370-9416
 800-369-7769 209-532-7201 FAX 209-532-1211
cameronmicrodrillpress.com