



Shown: Model 704-A1 with Yukiwa
5/32" key type chuck.

New Cameron Series 704

Specifications:

- 1/7th HP heavy duty DC motor
- Interchangeable spindle with linear sealed bearings for quick and easy spindle change. (No longer needs oiling)
- Variable speed control unit (5 amp / 115 VAC) maintains speeds from 1000-30,000 rpm.
- Working area: 6 7/8" wide and 11 3/8" deep
- Distance from spindle center to edge of columns: 8"
(Drill to the center of a 16" workpiece.)
- Max distance from chuck to base: 5"
 - Extended columns available. (Part #DT24A) Specify distance needed from chuck to base.
- Overall dimensions:
 - Height: 18 1/2" (on models with indicator)
 - Width: 7 1/8"
 - Depth: 13 1/8"
- Max spindle feed travel: 1 1/4"
- Clear belt safety guard for easy viewing of belt & pulley area

Models available:

- A-1** Yukiwa 5/32"
- B-1** Yukiwa 5/32" and 1/2" Travel Dial Indicator
- C-3** Yukiwa 0-1/8" Keyless Chuck
- D-3** Yukiwa 0-1/8" Keyless Chuck and 1/2" Travel Dial Indicator
- CS** **Collet System:** 1/8" Collet, VSC, Dial Indicator